

PRIMARY CORNER DESCRIPTION Tsp. Cor. for 31 & 32 S., R1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7481-82 & Vol. 26 Page 11159)

-----  
The cor. to Tps. 31 & 32 S, R1E, which is a basalt stone, 30x15x6", 24", in the ground, marked WM on W face, with 6 notches on N, S, E, & W faces, from which,  
A fir, 36" dia., bears N.10°E., 58 lks. mkd: WM T31S R1E S31 BT.  
A fir, 35" dia., bears S.45°E., 63 lks. mkd: WM T32S R1E S6 BT.  
A fir, 35" dia., bears S.81°W., 76 lks. mkd: WM T32S R1W S1 BT.  
A fir, 15" dia., bears N.32°W., 23 lks. mkd: WM T32S R1W S36 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7503)

-----  
Cor. of Tps. 31 and 32 S., R1E., only, which is a basalt stone, firmly set, 6x14x6 ins. above ground marked with 6 notches on N., S., E., and W. edges, from which  
A Fir 36" dia., bears N.10°E., 58 lks. dist. mkd. W M T31S R1E S31 BT. (Old BT)  
A Fir 35" dia., bears S.47°E., 63 lks. dist. mkd. WM T32S R1E S6 BT. (Old BT)  
A Fir 35" dia., bears S.81°W., 78 lks. dist. mkd. WM T32S R1W S1 BT. (Old BT)  
A Fir 15" dia., bears N.32°W., 23 lks. dist. mkd. WM T31S R1W S36 BT. (Old BT)  
I obliterate the marks on the bearing trees referring to Tps. 31 and 32 S., R1W., and re-mark the stone 31S on N., 32S on S., and 1E on E. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-31

-----  
Found - 30 x 15 x 6 stone at corner with 6 notches on N., S., E., and W. sides.  
36" D.Fir now snag, N.10°E., 38.3 ft., bark scribe, good face.  
15" D.Fir, now down, N.32°W., 15.2 ft.  
35" D.Fir, now down, S.81°W., 51.5 ft., shows good scar.  
35" D.Fir, now stump, S.45°E., 41.6 ft.

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 700650

PRIMARY CORNER DESCRIPTION Tsp. Cor. for 31 & 32 S., R1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R	Doug.Co.
1	S 31	1	
W	S 6	E	
	T 32 S		Jack.Co.

New BTs- 8" Maple N.8°W., 48.0 ft. mkd. T32S R1W S1 CS BT.  
9" D.Fir N.75°E., 49.6 ft. mkd. T31S R1E S31 CS BT  
6" Yew S.23°E., 25.3 ft. mkd. T32S R1E S6 CS BT.  
Cor. is 20.0 ft. West of ravine.