

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1 (SE. Cor. S. 36, T31-1)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7482)

 Set a basalt stone 35x15x5 ins., 24" in the ground on top of the Umpqua Divide, for closing cor. to secs. 1 and 36, mkd. C.C. on W. face, with 6 notches on N., S., and W. edges, from which

- A Fir 30" dia., bears N.41°E., 28 lks. dist. mkd. CC T31S R1E S31 BT.
- A Fir 60" dia., bears S.30°W., 2 lks. dist. mkd. CC T32S R1W S1 BT.
- A Fir 40" dia., bears N.74°W., 42 lks. dist. mkd. CC T31S R1W S36 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7504)

 At the cor. of Tps. 31 and 32 S., R1W., which is a basalt ston, firmly set, 6x15x5 ins. above ground, marked with CC on W., and 6 notches on N., S., and W. face, from which

- A Fir 30" dia., bears N.41°E., 28 lks. dist. mkd. CC T31S R1E S31 BT. (Old BT)
- A Fir 60" dia., bears S.30°W., 2 lks. dist. mkd. CC T32S R1W S1 BT. (Old BT)
- A Fir 40" dia., bears N.74°W., 42 lks. dist. mkd. CC T31S R1W S36 BT. (Old BT)

I obliterate the marks on the bearing tree referring to T31S R1E, and re-mark the stone 31S on N.; CC R1W and 6 grooves on W.; and 32S on S. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 9, 1968 - C.S. File 54/71-32

 Found - 35x15x5 stone mkd. CC and 6 notches.
 60" now 64" D.Fir S.30°W., 1.3 ft., shows good scar.
 30" D.Fir now rotten stob, N.41°E., 18.5 ft.
 40" D.Fir now rotten stob, N.74°W., 27.7 ft.

Set Brass cap at cor. mkd: County Surveyors Office
 T 31 S Doug. Co.
 R S 36 | S31 R
 1 S 1 | C.C. 1
 W Jack. Co. E

New BTs- 9" D.Fir N.2½°E., 11.5 ft. mkd. T31S R1E S31 CC CSBT
 9" D.Fir N.26°W., 17.2 ft. mkd. T31S R1W S36 CC CSBT