TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8288)

Set a granite stone 24x12x8 ins., 18" in the ground for cor. of secs.19, 24, 25 and 30, marked 2 notches on the S. and 4 notches on the N. edges, from which

A Fir 24" dia., bears N.52½°E., 7 lks. dist.mkd. T32S R2W S19 BT.
A Fir 16" dia., bears S.15°E., 8 lks. dist. mkd. T32S R2W S30 BT.
A Fir 14" dia., bears S.74°W., 30 lks. dist. mkd. T32S R3W S25 BT.
A Fir 14" dia., bears N.79½°W., 45 lks. dist. mkd. T32S R3W S24 BT.

GLO survey by Fred Mensch, U.S. Surveyor, under Special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8357)

Intersect the old cor. of secs. 19, 24, 25 and 30, which is a stone firmly set, marked and witnessed as described the surveyor general and which I now change to refer to secs.19 and 30, T32S R2W only, and destroy marks on BTs referring to R3W.

Survey by Glenn S. Baughman - For: U.W. Forest Service - Aug. 1968 - C.S. File 55/87-1

Found - Stone 24"x12"x5" with 2 notches on S. and 4 notches on N. edges.
Orig. 24" now 34" Fir, bears N.52°E., 4.0 ft. with scribes in poor condition.

Set 2" x 30" I.P. with brass cap stamped:

T 32 S
R3W S 24 | S 19 / S 30 ~~CC~~ R2W
1968
OLS 536

From the pipe monument, the orig. BT is:
34" Fir bears N.52°E., 4.0 ft. remarked "T32S R2W S19 BT"

New BT - 22" Fir bears S.38°E., 22.5 ft. mkd. T32S R2W S30 BT.

Placed BT tags on all BTs and facing the monument.
(Letter in C.S. File 55/87 from BLM states that they would not call this corner as "closing".)