TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 100331

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 24 only, T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, U.S. Surveyor, Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8357)

Set a slate stone 18x12x4 ins., 12" in ground for ¼ sec. cor. of sec. 24 only, marked ¼ on W. face, from which
A Madrona 12" dia., bears S.36°W., 83 lks. dist. mkd. ¼ S24 BT.
A Fir 6" dia., bears N.34°W., 40 lks. dist. mkd. ¼ S24 BT

Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-18

Found - Orig. stone 18"x12"x4" marked "¼" on W. face.
Orig. 12" now 20" Madrona with open face, scribes in poor condition, bears S.36°W., 54.9 ft.
Set 2" x 30" I.P. with brass cap stamped: T 32 S
R3W ¼ R2W
S 24
1968
OLS 536
From the pipe monument, I marked the trees:
27" Fir bears N.33°W., 25.5 ft. mkd. ¼ S24 BT.
12" Fir bears S.6°E., 15.3 ft. mkd. ¼ S24 BT.
Placed BT tags on all BTs and facing the monument.