

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 19 Page(s) 8288)

-----  
Set a sandstone 15x12x10 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 10" dia., bears S.21°E., 71 lks. dist. mkd. ¼ S19 BT  
A Hemlock 10" dia., bears N.53¼°W., 103 lks. dit. mkd. ¼ S24 BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8357)

-----  
Set a slate stone 16x8x8 ins., 11" in ground for ¼ sec. cor. of sec. 19, T32S R2W only, marked ¼ on E. face, from which  
A Fir 8" dia., bears N.44°E., 26 lks. dist. mkd. ¼ S19 BT  
A Fir 6" dia., bears S.85°E., 12 lks. dist. mkd. ¼ S19 BT

Survey by Glenn S. Baughman - For: U.S. Forest Service - July 1969 - M 38-38

-----  
Found - 22" Fir bears N.44°E., 26 lks., scribe visible.  
12x8x4 ins. stone "S" mkd. on top.  
18" Fir bears S.85°E., 12 lks., scribe visible.  
Set 2" x 30" galv. I.P. with brass cap stamped: ¼ Cor. S 19 1969 OLS 536.  
Scribed- 12" Hemlock bears S.80°E., 23.8 ft., tagged.  
(¼ corner for sec. 24, T32-3, brass cap & orig. stone, bears S.1°03'55"W., 612.95 ft.)