

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 19 Page(s) 8289)

Set an iron stone 24x15x10 ins., 18" in ground for cor. of secs. 7m 12, 13 and 18 marked with 2 notches on N. and 4 notches on S. edges, from which

A Pine 12" dia., bears N.36°E., 41 lks. dist. mkd. T32S R2W S7 BT.

A Pine 10" dia., bears S.71½°E., 105 lks. dist. mkd. T32S R2W S18 BT.

No other trees in limits. Mound and pits impracticable on account of steepness of ground.

Tied corner in GLO survey by Fred Mensch, contract #757, dated Sept. 14, 1904 - DCSO records, Vol. 20 Pg. 8385

Survey by Don E. Garrett - For: U.S. Forest Service - March 24, 1972 - M 44-62

Found - 25" x 15" x 10½" iron stone by staff compass & chain, irregular notches on N. & S. faces.

Old BTs destroyed by fire.

Set brass cap at stone & re-deposited stone alongside. Cap stamped: 1972

T32S T32S
R3W S13 S 7 R2W
S 18

P.L.S. 544

Established bearing trees:

17" Fir bears N.26°E., 21.8 ft. scribed S7 BT.

24" Fir bears S.40°E., 20.6 ft. scribed S18 BT.