

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 100509

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13, T32-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8385)

-----  
At the point of intersection, is an iron rock in place, 12x12x10 ins. above ground, for closing cor. of secs.12 and 13, I mark CC on W. with 2 grooves on N. and 4 grooves on S. face, from which

An Alder 16" dia., bears N.60°W., 69 lks. dist. mkd. T32S R3W S12 BT.

A W.Fir 24" dia., bears S.23°W., 57 lks. dist. mkd. T32S R3W S13 BT.

No bearing trees at former cor. referring to these secs.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-19

-----  
Found - 12x12x8" stone with CC marked on the W. face.  
Orig. 16" now 18" Alder bears N.60°W., 45.5 ft. with open face, scribes in poor condition.

Set 2" x 30" I.P. with brass cap stamped; T 32 S  
R 3 W CC     S 12 | S 7     R 2 W  
                  S 13 |  
                  1968  
                  OLS 536

From the pipe monument, I marked:

6" Hemlock bears N.57°W., 63.5 ft. mkd. T32S R3W S12 CC BT.

48" Fir bears S.23°W., 60.6 ft. mkd. T32S R3W S13 CC BT.

Set BT tags on all bearing trees and facing the monument.

**See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are not available on the internet.**