

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 7 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8290)

A Fir 10" dia. for ¼ sec. cor. mkd. ¼ S12 on the W. and S7 on the E. face, from which
A Fir 12" dia., bears S.60°E., 45 lks. dist. mkd. ¼ S BT.
A Fir 12" dia., bears N.70°W., 13 lks. dist. mkd. ¼ S BT.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-4

Found - Orig. 12" now 16" Fir mkd. "¼ S7" on E. face.
Orig. 12" now 16" Fir mkd. "¼ S BT" bears N.62°W., 13.7 ft.

Set 2" x 30" I.P. with brass cap mkd. T 32 S
R3W ¼ | S 7 R2W
1968
OLS 536

From the pipe monument, the orig. BT is:
16" Fir bears N.62°W., 13.7 ft. mkd. "¼ S BT".
New BT - 20" Fir bears S.59°E., 26.0 ft. mkd. "¼ S BT"
Placed BT tags on all BTs and facing the monument.

Douglas Co. Surveyors Office - S.J. Flause, Deputy - T.R. Plouff, crew - Feb. 26, 1981 - C.S. File 61/24-1

Found - 1902 Corner tree marking the W. ¼ of sec. 7 only, originally a 10" Fir, now 16" (DBH) D.Fir. This tree has an opened blaze on E. face, with scribing "S7" visible. Also, on this face is nailed a bronze washer with markings "2741".
From this tree, a 2½" B.C. on a 2½" I.P. (O.D.) protruding 21" from ground & firmly set bears S.83°E., 2.5 ft. per M 44-62. The found brass cap is mkd. "¼ | S7 1968 OLS 536".
Orig. BT, 12" Fir, now 16", bears N.72°W., 16.2 ft. Partially healed blaze, has fragmentary scribing visible. "/4S"
20" Fir with healed blaze, bears S.59°E., 26.5 ft.
New BT - 11" D.Fir scribed "WC ¼ S7 CS BT" bears N.40°E., 22.6 ft.