

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8292)

-----  
Set an ironstone 24x12x10 ins., 18" in ground for ¼ sec. cor. mkd. ¼ on the W. face, from which  
A Fir 24" dia., bears S.2°E., 300 lks. dist. mkd. ¼ S6 BT  
A Fir 24" dia., bears N.13°W., 91 lks. dist. mkd. ¼ S1 BT.

Tied this corner in GLO survey by Fred Mensch, Contract #757, dated Sept. 14, 1904 - (DCSO records, Vol. 20, Pg.8354)

Survey by Don E. Garrett - For: U.S. Forest Service - March 24, 1972 - M 44 - 62

-----  
Found - Ironstone, "W ¼" clearly marked on W. face.  
Old BT, N.13°W., 91 lks., fallen down with rotten stump standing, faint traces of scribing still visible.  
Two large D.Firs stand in position of old SE BT., did not open: 41" D.Fir S.1°54'E., 191.0 ft.  
35" D.Fir S.3°23'E., 195.2 ft.  
Set brass cap with stone alongside, stamped: T 32 S  
R3W R2W  
S 6 ¼  
1972  
RPLS 544  
New BTs- 17" Fir S.19°E., 55.9 ft. scribed ¼ S6 BT.  
8" Fir N.27½°E., 13.0 ft. scribed ¼ S6 BT.