

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 134700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7610)

Set a granite stone 24x12x4 ins., 18" in the ground for cor. of secs. 31 and 32 marked with 5 notches on E. and one notch on W. edges, from which
A Fir 12" dia., bears n.5½°E., 18 lks. dist. mkd. T31S R2W S32 BT.
A Fir 30" dia., bears N.43°W., 124 lks. dist. mkd. T31S R2W S31 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7617) ; 7626 ; 7649)

(Page 7617)
The cor. of secs. 31 and 32, which is basalt stone 6x10x4 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.
(Page 7626)
The old cor. of secs. 31 and 32
I destroy the cor. and marks on bearing trees.

(Page 7649)
Intersect So. bdy. of T31-2, 34.13 chs. N.89°58'E. of the closing cor. of T32S., Rs. 2 & 3 W.
Set a granite stone 14x10x6 ins., 9½" in the ground for closing cor. of secs. 31 and 32, mkd. CC on N. with 5 grooves on E. and 1 groove on W. face, from which
A Fir 20" dia., bears N.30°E., 77 lks. dist. mkd. T31S R2W S32 BT.
A Madrone 12" dia., bears N.52½°W., 54 lks. dist. mkd. T31S R2W S31 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones; Terry Connell, crew - Aug. 1966 - C.S. File 54/28-109

Found - 14x10x6 stone "CC" on N. face.
20" now 31" D.Fir N.30°E., 50.8 ft., shows good scar.
12" now 17" Laurel N.52½°W., 35.6 ft., rotten face, scribe visible, "31 R2W S31 BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R
S 31 | S 32 2
S 6 W
1966

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 134700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 11" Laurel N.32°W., 27.6 ft. mkd. T31S R2W S31 CSBT.
Best way to corner is on old trail from Neuman Gap, location tag on trail.

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-25 A-H (see also revised map M166-35 A-H)

Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1966
15" G.Fir set tag dated 8/14; S.66°W., 13.2' to nail side center.
10" G.Fir set tag dated 8/14; S.44°E., 24.6' to nail side center.
16" Madrone with healed face and tag dated 8/66; N.32°W., 27.6' to nail side center
17" Madrone healed face and tag dated 8/66; N.52½°W., 35.6' to nail side center.