TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8345

Set a basalt stone 24x12x4", 18" in the ground for ¼ sec. cor. mkd. ¼ on N face. Raise mound of stone, 3 ft. base, 2 ft. high N. or cor. Pits impracticable.

Glenn S. Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-6

Found - Stone 24x12x4" marked "¼" on N. face and mound of stone north of corner.

Set - 2"x30" galv. IP with Brass Cap, stamped: T32S R2W
¼ S 18
S 19
1968 OLS 536

From the Pipe Monument, I marked the following trees:
32" Fir bears N.15°W. 41.8 ft. Mkd: "¼ S18 BT".
28" Fir bears S.4°E. 23.9 ft. mkd: "¼ S19 BT".
Placed BT tags on all bearing trees and facing the monument.