

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7611)

-----

Set granite stone 12x12x5 ins., 8" in the ground for ¼ sec. cor. marked ¼ on the N. face, from which  
 A Fir 20" dia., bears N.60°E., 42 lks. dist.mkd. ¼ S32 BT.  
 A Fir 20" dia., bears N.64½°W., 17 lks. dist. "¼ S32 BT."

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7617 and 7627)

-----

(Page 7617)  
 The Qr. sec. cor. on South bdy. of sec. 32, which is a baalt stone 4x10x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.  
 Page 7627)  
 (39.75 chains)  
 Set a granite stone 15x12x6 ins., in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which  
 A Fir 20" dia., bears N.30°E., 77 lks. dist. mkd. ¼ S32 BT  
 A Madrone 12" dia., bears N.57½°W., 54 lks. mkd. ¼ S32 BT.  
 (42.31 chains)  
 The old ¼ cor., I destroy the cor. and marks on brg trees.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & C. Stone - Sept. 1966 - C.S. File 54/28-87

-----

Found - No trace of corner stone.  
 20" D.Fir, now stump, N.30°E., 50.8 ft. (find this **N.30°W.**, 50.8 ft.), scribe visible "¼ S32 BT" by ring count this was done about 1900. (Orig. 1908)  
 Parts of Laurel, N.57½°W., 35.6 ft. (find this to be **N.57½°E.**)  
 Also, by chaining between the ¼ cor. sec. 32 only and sec. cor. for 5 & 6, T32-2, I find dist. to be 292.8 ft. Orig. notes call for 274.6 ft. Difference is 18.2 ft.  
 This corner lies in clear cut unit. Not having anything to scribe, I tag orig. stump N.30°W., 50.8 ft. Also, C.C. of secs. 5 & 6 T32-2 bears East 292.0 ft.  
 Set Brass cap at cor. mkd:

County Surveyors Office  
 T 31 S R 2 W  
 ¼     S    32      
           T 32 S

cont.

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 174700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

James Klein - For: Williams/Pacific Connector Gas Pipeline  
Project - 4/2015 - M166-35 A-H

-----  
Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1966  
30" dia. 3' tall stump with hack marks N.30°W.,  
50.8'

New BTs- 13" Fir (mkd CS¼ S6 BT) **SET** tag dated 3/15  
(S.238°E., pg 1/8 - S.38°E., pg 2/8?) - 12.95' to  
nail side center

12.5" Fir (mkd - CS¼ S32 BT) **SET** tag dated 3/15  
N.08°W., 19.1' to nail side center