TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8343-4

Set an ironstone 18x10x6", 12" in the ground for cor. of secs. 17, 18, 19, & 20 mkd with 3 notches on S & 5 notch(es) on E edges, from which

A fir, 36" dia., bears N.24½°E., 11 lks., mkd: T32S R2W S17 BT.
A for, 42" dia. bears S.69°E. 52 lks. mkd: T32S R2W S20 BT
A fir, 28" dia., bears N.19½°W., 153 lks., mkd: T32S R2W S18 BT.
No SW tree in limits. Mound & pits impracticable.

Glenn S. Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-8

Found - Stone 18x10x6" with 3 notches on S. & 5 notches on E. edges.
Orig. 36" Fir, now snag, with good scribes bears N.35°E., 7.3 ft.

Set - 2"x30" galv. IP with Brass Cap, stamped: T32S R2W

S 18	S 17
S 19	S 20

1968 OLS 536

From the Pipe Monument, I marked a:
20" Hemlock T32S R2W S17 BT bears N.67½°E., 58.0 ft.
8" Fir T32S R2W S20 BT bears S.22°E., 33.2 ft. (Placed BT tags on all)
16" Fir T32S R2W S19 BT bears S.25°W., 47.2 ft. (bearing trees, & facing monument.)
10" Fir T32S R2W S18 BT bears N.58°W., 32.0 ft.