

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8351)

Intersect S. bdy. of T31-2, 160 lks. East of the ¼ sec. cor. on the S. bdy. of sec. 32.

At point of intersection, Set an ironstone, 24x10x4 ins., 18" in ground, for closing cor. of secs. 5 and 6, marked C.C. on S. face, with 1 groove on W. and 5 grooves on the E. faces, from which

A Fir 14" dia., bears S.44°E., 41 lks. dist. mkd. T32S R2W S5 BT.

A Fir 20" dia., bears S.31½°W., 16 lks. dist. mkd. T32S R2W S6 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7617)

The cor. of secs. 5 & 6, T32-2, which is an ironstone 6x8x4 ins. above ground firmly set, mkd. and witnessed as described the by surveyor general.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-85

Found - 14" D.Fir now 20" stump, 6.6 ft. high, S.44°E., 27.1 ft. Tree had been opened and burnt. Faint scribe marks visible.

20" D.Fir now stump, S.31½°W., 10.6 ft., opened for scribing.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W
S 32

S 6 S 5
T 32 S

This cor. lies in clearcut unit. BT stumps are cut high. cor. No new trees to scribe so tagged orig. stumps on top & sides. Reblazed and rescribed:

20" D.Fir stump S.44°E., 27.1 ft. mkd. T32S R2W S5 CS BT.

Corner lies on top of small ridge about 250.0 ft. South and West of cutting lines and about 300.0 ft. N. of badly eroded area.

continued next page

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-25 A-H (see also revised map M166-35 A-H)

- Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1966
- 19" D.Fir 10' stump with visible scribe and tag dated 9/66; S.44°W., 27.1'
- 32" D.Fir 10' stump with visible scribe and tag dated 9/66; S.21½°W., 10.6'
- New - 13" D.Fir set tag dated 8/14; S.66°E., 18.6' to nail side center
- 10" D.Fir set tag dated 8/14; S.73°W., 1.2' to nail side center
- 15" D.Fir set tag date 8/14; N.21°W., 17.85' to nail side center.