TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8344

Set a granite stone 24x12x5", 18" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 28" dia., bears S.30°W., 45 lks., mkd: ¼ S20 BT.
A sugar pine, 30" dia. bears N.10°W. 32 lks. mkd: ¼ S17 BT

Glenn S. Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-9

Found - Stone 24x12x5" mkd. "¼" on the north face.
Orig. 28", now 36" Fir, bears S.30°W. 28.3 ft., with closed face.
Orig. 30", now 40" Sugar Pine, bears N.10°W. 20.1 ft., opened the face and found scribes in good condition.

Set - 2"x30" galv. IP with Brass Cap, stamped: T32S R2W
¼ S 17
S 20
1968 OLS 536

Placed BT tags on all bearing trees and facing mont.