

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Jackson Co. Surveyors Office - Edward McGinty, Co. Surveyor -
R. Frost & S. Beecher Techs - Sept. 7, 1988 - C.S. File
63/82-7

Found - Projecting 15" the 2" dia galv IP in mound of stone,
with 3" dia. brass cap, mkd as recorded (in) 1968
The original 18x8x8" stone, mkd. "1/4" by C.
Campbell in 1902 is fd. lying alongside the brass
cap. Add mks. "T32SR2W CS 1988" to above noted
brass cap which now reads: T32S R2W
1/4
S 20|S 21
1968
OLS 536
CS 1988

from which original BTs found:

Fir stump remains fd. at record location of original
NE BT. Nearby is fd. axed out (fir) face scribed
"1/4S2 B".

Sawed Fir stump, 42" dia., scribed "1/4S2" in partly
exposed face) brs. record; S.23°W., 27.06 ft. to
center of stump.

BT mkd. on the above noted survey, now a sawed fir
stump, 10" dia., containing (partial) scribed
"BT" in partly exposed face, brs. S.49°E, 7.6 ft.
(Rec; S.48°E., 7.3 ft.)

BTs apparently mkd. by Douglas County Surveyor
(currently not of record in this office) fd. and
measured to center of trees at lower blaze:

D.Fir, 12" dia. scribed "1/4S21 CS" & "BT" brs.
S.34 1/2°E., 5.4 ft.

D.Fir, 9" dia., scribed "1/4S20 CS" & "BT" brs.
S.56°W., 23.0 ft.

Chinquapin, 13" dia., scribed "1/4S20 CS" & "BT" brs.
N.57°W., 17.3 ft.

The center of found spike, thru bearing tree tag,
atop a 68" dia. sawed fir stump, brs. N.43°E.,
34.3 ft.

The peak of MT McLaughlin an estimated 40 miles distant, brs
S.65°E.

Corner lies near the Northeast edge of standing timber at the
corner of southerly and westerly edge of large clear cut.

V=18°