

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8331

-----  
Set a basalt stone 12x12x9", 10" in the ground for cor. of secs. 16, 17, 20, & 21 mkd with 3 notches on S & 4 notches on E edges, from which  
    A fir, 34" dia., bears N.80°E., 184 lks., mkd: T32S R2W S16 BT.  
    A fir, 30" dia., bears N.89¾°W., 298 lks., mkd: T32S R2W S17 BT.  
No other trees in limits. Raise mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Pits impracticable.

Glenn S Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-12

-----  
Found - A stone, well eroded.  
    Orig. 34", now 40" fir with open face, bears N.80°E., 121.4 ft.  
Set - Brass cap on 2"x30" galv. IP stamped      T32S R2W  
  S 17|S 16  
  S 20|S 21  
From the pipe monument, I marked                   1968 OLS 536  
    12" Fir bears N.27°E., 11.6 ft. mkd: T32S R2W S16 BT  
    13" Fir bears S.41°E., 44.7 ft. mkd: T32S R2W S21 BT  
    15" Fir bears S.18°W., 43.8 ft. mkd: T32S R2W S20 BT  
    15" Fir bears N.42°W., 9.9 ft. mkd: T32S R2W S17 BT  
Placed BT tags on all BTs and facing the monument.