TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8331

Set a basalt stone 18x12x5", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 60" dia., bears S.60°E., 33 lks., mkd: ¼ S21 BT.
A fir, 12" dia., bears N.35°W., 57 lks., mkd: ¼ S16 BT.

Glenn S Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-13

Found - Stone 18x12x5" marked "¼" on the north face.
Orig. 60" Fir now snag with burnt face, bears S.60°E., 21.7 ft.
Set - 2"x30" galv. IP with brass cap stamped T32S R2W
¼ S 16 / S 21
1968 OLS 536
From the pipe monument I marked the following trees:
13" Fir bears N.53°E., 14.3 ft. mkd: "¼" S16 BT.
8" Fir bears S.58½°E., 10.5 ft. mkd: "¼" S21 BT.
Placed BT tags on all BTs & facing the monument.