

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7612-13)

Set an ironstone 18x12x10 ins., 12" in the ground for ¼ sec. cor. mkd. ¼ on the N. face, from which
A Fir 12" dia., bears N.30°E., 27 lks. dist. mkd. ¼ S34 BT
A Fir 10" dia., bears N.35°W., 23 lks. dist. mkd. ¼ S34 BT

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616 and 7629)

(Page 7616) The ¼ sec. cor. on S. bdy. Sec. 34, which is an ironstone 6x10x10 ins. above ground, firmly set, and mkd. and witnessed as described by the surveyor general.

(Page 7629) (40.16½ chs.) Set a granite stone 12x10x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which

A Fir 8" dia., bears N.10°E., 71 lks. dist. mkd. ¼ S34 BT
A Madrone 10" dia., bears N.75°W., 38 lks. dist. mkd. ¼ S34 BT.

(43.85 chs.)

The old ¼ sec. cor.

I destroy the cor. and marks on bearing trees.

BLM Mineral Survey No. 975 A&B, surveyed by Walter L. Gonna son, Mineral Surveyor, surveyed March/Sept. 1963 - (DCSO records Vol. 38 Page(s) 15705)

The S. corner of Sec. 34, T31S R2W WM bears West 342.21 ft. distance from closing corner, Secs. 3-4, T32S R2W WM. The old rock as described in the official record was found to be fractured and the bearing trees non-existent. I reset with a 1/2" pipe, 24" long, 18" in the ground with a 3" dia. brass cap, mkd. S 34, T31S R2W; from which

A madrona, 16" dia., bears N.60°W., 23.4 ft., mkd. ¼ S34 T31S R2W BT.

A fir, 28" dia., bears S.69°E., 26.5 ft. mkd. ¼ S34 T31S R2W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & C.Stone, crew - Sept. 14, 1966 - C.S. File 54/28-88

CORNER REPORT ONLY

Found - 3" brass cap on ½" iron pipe mkd. 34 31-2 ¼ and tag on tree set by Williams July 14, 1965.

continued next page

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 376700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No trace of original corner.
17" Laurel N.5½°W., 31.8 ft. mkd. T31S R2W S34 ¼ BT.
39" D.Fir S.70°E., 23.0 ft. mkd. ¼ BT, other
scribing not legible.