

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L Campbell Deputy Surveyor under Contract #747 dated May 5, 1902 - (DCSO rec Vol. 20 Pg 8320

Set an ironstone 18x12x6", 12" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A fir, 10" dia., bears S.15°E., 23 lks., mkd: 1/4 S21 BT.

A fir, 14" dia., bears S.19 1/2°W., 48 lks., mkd: 1/4 S20 BT. N.0°02'W., 1.12 chs: A fir, 60" dia., on line, I mark with 2 notches on N & S sides (Orig. notes say S20 & 21 S.B. 21 & 22)

Glenn Baughman - For: USFS - Aug. 1968 - C.S. File 55/87-14

Found - Stone 18x12x6" marked "1/4" on west face.

Orig. 14" now 24" Fir with scribes in poor condition, bears S.24°W., 31.0 ft.

Set - 2"x30" galv. IP with brass cap stamped T32S R2W

1/4

S 21 | S 22

From the pipe monument I marked: 1968 OLS 536

15" W.Fir bears N.68°E., 20.7 ft. mkd: "1/4 S22 BT"

24" Fir bears S.24°W. 31.0 ft mkd: "1/4 S21 BT" (remarked)

Placed BT tags on all BTs and facing the monument.

Jackson Co. Surveyors Office - Edward McGinty, Co. Surveyor - R. Frost and S Beecher, Techs - 9/1/1988 - C.S. file 63/82

1/4 corner common to Sec. 21 & 22, T32S R2W W.M. Corner being on the county line between Jackson and Douglas Counties.

Found - Projecting 15", the 2" dia. galvanized IP, with 3" dia. brass cap (set for the corner on survey C.S. 55/87 dated 1968)

The orig. 18x10x7" stone, mkd "1/4" as recorded by C.L. Campbell in 1902, lying alongside.

An original BT, a D.Fir, now 28" dia. with axed out partial face fd. inside tree, containing partial scribed "4,S&BT", brs. record S.19 1/2°W., 31.68 ft. to estimated original position of scribed face. This tree was reported remarked" on the above noted survey and this scribed face is now healed. Re-measure; S.21°W, 32.5 ft. to center of tree at base. Record (C.S. 55/87); S.24°W, 31.0 ft.

The record location of the original SE BT falls in old skid trail.

A BT mkd. in 1968, now a fir stump, 20" dia., scribed "BT" in partially exposed face, brs. N.68°E., 20.95 ft. to center. Record; 20.7 ft.

continued next page

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - Add mks. "T32S R2W" C.S. 1988 to BC
Mk new trees "CS""BT" and take measurements to center of trees at lower blaze;
I.Cedar, 6" dia. brs. S.23°E., 9.0 ft.
W.Fir, 15" dia., brs. N.76°W, 46.4 ft.
Note - The original "line tree" recorded to be 1.12 chains North is now a sawed fir stump, 66" dia., with no line blazes visible. Corner lies on small logged over bench, about 20 ft. North of skid trail.
V=18½°

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-25 A-H (see also revised map M166-35 A-H)

Found - 2½" brass cap stamped OLS 536, 1968 and CS 1988
15" Cedar with healed face and tag dated 10/13;
S.23°E., 9.0' to nail side center
24" D.Fir with tag dated 10/13; N.76°W., 46.4' to nail side center