TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8320

Set a basalt stone 24x12x10", 18" in the ground for cor. of secs. 15, 16, 21, & 22 mkd with 3 notches on S & E edges, from which

A fir, 14" dia. bears N.74°E., 57 lks mkd: T32S R2W S15 BT
A fir, 36" dia., bears S.59½°E., 43 lks., mkd: T32S R2W S22 BT.
A fir, 10" dia. bears S.6°W., 12 lks. mkd: T32S R2W S21 BT
A fir, 30" dia., bears N.27½°W., 31 lks., mkd: T32S R2W S16 BT.

Glenn Baughman - USFS - Aug. 1968 - C.S. 55/87-15

Found - Stone 24xl2x10" with 3 notches on S. and E. edges.
Orig. 14", now 27" Fir, with open face & in good condition, bears N.74°E. 39.1 ft.
Orig. 10", now 14" Fir, with scribes in poor condition, bears S.6°W. 7.9 ft.
Orig. 30" Fir, now stump with open face, bears N.27½°W. 20.5 ft.

Set - 2"x30" Galv. IP with Brass Cap, Stamped: T32S R2W

S 16	S 15
S 21	S 22

1968 OLS 536

From the pipe monument, the Orig. BTs. are:
27" Fir bears N.74°E., 39.1 ft. mkd: T32S R2W S15 BT
14" Fir bears S.6°W. 7.9 ft. mkd: T32S R2W S21 BT. (remarked)

New BTs- 8" Fir bears N.22½°W. 11.5 ft. mkd: T32S R2W S16 BT.
9" W.Fir bears S.31°E. 9.0 ft. mkd: T32S R2W S22 BT.