

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8322

Set an ironstone 28x10x8", 21" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 12" dia., bears N.80°E., 24 lks., mkd: ¼ S15 BT.
A sugar pine, 40" dia. bears S.70°W., 14 lks mkd: ¼ S16 BT
N.0°02'W., 9.10 chs
A Fir, 28" dia., on line, I mark with 2 notches on N. & S. sides.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - 8/3/1970 - C.S. File 54/117-8

Found - Corner Stone, mkd: "¼" on W face, in place, as called for.
Orig. 12", now 18" Fir, alive N.80°E. 15.8 ft scribe visible on previously opened blaze. We tag.
Orig. 40", now 44" S.Pine, alive, S.70°W. 9.2 ft., we open & find "S16 BT"
Set - Brass Cap at Cor. mkd: County Surveyors T32S R2W
(Reset Old Stone Alongside) Office, 1970 ¼ S 16|S 15
New BTs- 14" Hemlock S.44°W. 26.0 ft. mkd: "¼ S16 CS BT".
9" D.Fir S.41°E. 19.0 ft. mkd: "¼ S15 CS BT"
This corner lies on W. side of spur ridge at S. end of Talus area and large rock outcrop about 20 ft. high, & 30 ft. across.
Found - Line Tree 600 ft. to N. of ¼ Corner.