

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8322

-----  
Set a basalt stone 18x12x6", 12" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notches on E edges, from which  
A fir, 36" dia. bears N.75°E., 48 lks mkd: T32S R2W S10 BT  
A fir, 24" dia. bears S.46°E., 25 lks mkd: T32S R2W S15 BT  
A fir, 12" dia. bears S.48°W., 16 lks mkd: T32S R2W S16 BT  
A fir, 14" dia. bears N.64°W., 25 lks. mkd: T32S R2W S9 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - 8/3/1970 - C.S. File 54/117-7

-----  
Found - No trace of Corner Stone.  
Orig. 14", now 18" Fir, alive, N.64°W., 16.5 ft. (Rec. N.64°E.) We open & find scribe "2W".  
Orig. 24" Fir, now 26" Stump, S.46°E. 16.5 ft., scribe visible on log lying below stump.  
Orig. SW BT, down, and Orig. NE BT, gone.  
Set Brass cap at cor. mkd: COUNTY SURVEYORS T32S R2W  
OFFICE S 9 | S 10  
1970 S 16 | S 15  
New BTs- 14" W.Fir N.43°W., 25.0 ft. mkd: "T32S R2W S9 CS BT"  
14" D.Fir S.57°W., 10.1 ft mkd: "T32S R2W S16 CS BT"  
14" W.Fir N.21°E., 5.1 ft. mkd: "T32S R2W S10 CS BT"  
10" W.Fir S.10°E., 24.4 ft mkd "T32S R2W S15 CS BT",  
scribed 4 ft. above ground.  
This cor. lies on steep SW slope in logged unit.