

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8323

Set a basalt stone 18x10x5", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 24" dia., bears S.88°E., 27 lks., mkd: ¼ S10 BT.
- A fir, 30" dia., bears S.43°W., 44 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - M. Lenora Ladig - A. Vic Cangie - Karen Cheney - Aug. 5, 1976 - C.S. 59/18-16

Found - A 18"x10"x5" Ironstone with "¼" mkd. on West face. From which:

- A 24" now 40" Fir, bears S.88°E., 17.2 ft. Tree is alive with well healed blaze.
- A 30" now 36" Fir, stump bears S.43°W., 27.7 ft. (Call S.43°W., 29.0) with well healed blaze.

Set at true corner point: A 1"x36" IP with Brass cap stamped:
"Douglas Co. Surveyor T32S R2W
1976 ¼ S9|S10

Placed stone on West side of cap.

New BT - A 9" Yew bears S.58°W., 29.4 ft. scribed "¼ S9 CS BT" in single blaze.