

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 20 Page(s) 8326)

Intersect S. bdy. of T31S R2W, 160 lks. East of the ¼ sec. cor. on the S. bdy. of sec. 34.
At point of intersection, set an ironstone, 18x12x12 ins., 12" in ground for closing cor. of sec. 3 & 4, marked C.C. on the S. face, with 3 grooves on the E. and W. faces, from which
A Fir 24" dia., bears S.66°E., 38 lks. dist. mkd. T32S R2W S3 BT.
A Fir 12" dia., bears S.36°W., 29 lks. dist. mkd. T32S R2W S4 BT.

Fd. and used in GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & C.Stone, crew - Aug/Sept. 1966 - C.S. File 54/28-86

Found - 16x12x10 stone at corner with "CC" on S. face; 3 notches on E. face; 2 notches on W. face, firmly set in ground.
Orig. 24" now 31" D.Fir, S.66°E., 25.1 ft. (I find to be S.33°E.) Tree opened for scribe.
Orig. 12" D.Fir S.36°W., 19.1 ft. (I find to be S.60°W. 19.1 ft.) Tree opened for scribe "4BT".
Tree in good condition.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
S 34
S 4 | S 3
T 32 S
1966