

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8323

Set a basalt stone 28x12x4", 21" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 20" dia., bears S.10°W., 189 lks., mkd: ¼ S15 BT.
A fir, 16" dia., bears N.12½°W., 250 lks., mkd: ¼ S10 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - 8/11/1970 - C.S. File 54/117-6

Found - Corner Stone, in place, as called for with "¼" mkd. on N. side.

No trace of Orig. BT to NW due to old fire. At a point 124.7 ft. S.10°W., there is a hole & remains of old log. This matches the location of other Orig. BT & the call dist. from summit of divide to west fits this location, also.

Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R2W
(Reset stone alongside) OFFICE ¼ S 10
1970 S 15

New BTs- 12" D.Fir N.72°W. 13.0 ft. mkd: ¼ S10 CS BT
10" Cedar N.22°E. 18.4 ft. mkd: ¼ S10 CS BT
10" D.Fir S.48°E. 12.5 ft. mkd: ¼ S15 CS BT
9" W.Fir S.48°W. 9.0 ft. mkd: ¼ S15 CS BT

Mkd. 4 BTs due to density of and growth, this cor, lies on moderate northerly slope in very dense 2nd growth. Old Burn.