

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO rec Vol 20 Pg 8308  
-----

(From Cor. Secs. 22, 23, 26, & 27) N.0°02'W.

40.00 chs

Set an ironstone 28x12x10", 21" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 36" dia., bears S.25°E., 34 lks., mkd: ¼ S23 BT.

A fir, 28" dia., bears S.35°W., 10 lks., mkd: ¼ S22 BT.

41.25 chs

A fir, 36" dia., on line, I mark with 2 notches on N & S sides.

Jackson Co. Surveyors Office - Edward McGinty, Co. Surveyor - R. Frost & S. Beecher, Techs. - 8/11/1986 - C.S. 63/82-6  
-----

Found - Firmly set, the 20x12x10" sandstone, 5" above the ground mkd. "¼" on west face.

Set - Replaced found stone with and deposit it alongside a 1x36" galv. IP 30" in the ground, with a 2½" dia. brass cap mkd. "T32S R2W ¼S 22|23 CS 1986".

Found original BTs recorded by C.L. Campbell in 1902:

D.Fir snag, 28" diam., with single healed blaze bears record S.35°W., 6.6 ft. to center of tree at base.

The stump hole of tipped over D.Fir, 39" dia., with single healed blaze, bears record S.25°E., 22.44 ft. to center.

Mound stones around corner, mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

10" D.Fir bears N.76°E., 28.4 ft.

20" W.Fir bears S.8°W., 9.9 ft.

An orig. (1902) line tree, D.Fir 32" dia., with two blazes on the north and south sides bears North, 79.3 ft (Rec. 82.5 ft) Corner lies on south slope in heavy fir timber and along orig. blazed line.

Posted location tag on a D.Fir, 48" dia., at south edge of road approx. 20 chains north of quarter corner.

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-25 A-H (see also revised map M166-35 A-H)  
-----

Found - 2½" brass cap stamped CS 1986

12½" D.Fir with healed face and tag dated 8/86; N.76°E., 28.4' to nail side center

28" D.Fir 50' snag with healed face S.45°E., 7.5' no tag found or set. continued next page

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	19.5" D.Fir 30' snag with visible scribe and tag dated 8/86; S.10°W., 9.9' 10" D.Fir blazed and scribed set tag dated 8/14; N.55°W., 11.95' to nail side center