

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8309

Set an ironstone 28x15x8", 21" in the ground for cor. of secs. 14, 15, 22, & 23 mkd with 3 notches on S & 2 notch(es) on E edges, from which
A fir, 12" dia. bears N.83°E., 29 lks mkd: T32S R2W S14 BT
A fir, 16" dia. bears S.47°E., 32 lks mkd: T32S R2W S23 BT
A fir, 10" dia., bears N.19½°W., 20 lks., mkd: T32S R2W S15 BT.
No SW tree in limits.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - 6/15/1970 - C.S. File 54/117-1

Found - Orig. Corner Stone 28x15x8", 3 notches on S. & 2 notches on E., had been slightly disturbed.
Orig. 12" Fir Snag N.19½°W. 13.2 ft., scribing visible.
Orig. 19" Fir Stump N.83°E. 19.1 ft., good outer face, rotten inside.
No trace of S. E. nor S. W. Bearing Trees.
Set - Brass Cap at Cor. mkd: County Surveyors T32S R2W
Office S 15 | S 24
1970 S 22 | S 23
New BTs- 16" Hemlock N.49°E., 8.3 ft. scribed "T32S R2W S14 CS BT"
10" Hemlock S.49½°E. 51.8 ft. scbd: "T32S R2W S23 CS BT".
12" Cedar N.3°E. 40.7 ft. mkd: "T32S R2W S14 CS BT.
No tree In SW limits.