

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8313

-----

Set a basalt stone 24x15x8", 18" in the ground for cor. of secs. 2, 3, 10, & 11 mkd with 5 notches on S & 2 notches on E edges, from which

    A fir, 10" dia. bears N.20°E., 120 lks mkd: T32S R2W S2 BT

    A fir, 10" dia. bears S.70°E., 50 lks mkd: T32S R2W S11 BT

    A fir, 60" dia. bears S.18°W., 61 lks mkd: T32S R2W S10 BT

No NW tree in limits.

Douglas Co. Surveyors Office - Clell Goodwin - Vic Cangie - Lenora Lading - 6/9/1975 - C.S. 57/30-6

-----

Found - Weathered Basalt stone 6"x12"x18" with 4 recognizable notches on the south face.

    OBT 60" Fir stump bears S.18°W., 44.8 ft. (call: S.18°W., 40.3 ft) Cut into scar and find "S" scribe.

    Find possible BT N.12°E., 72.0 ft. (Call: N.20°E., 79.2 ft)

No trace of original S.E. ST

New - At corner as determined from one recognizable BT we set a Brass cap on 1½" Iron pipe marked

DOUGLAS COUNTY SURVEYOR

T32S  
3 | 2  
 10 | 11  
 R2W  
 1975

from which

Orig. 60" fir bears S.18°W., 40.3'.

Possible orig. 10" fir now 12" stump bears N.13½°E., 75.6'

New - 9" D.Fir scribed T32S R2W S11 CS BT in double scribe bears S.54°W., 11.2'

    9" D.Fir scribed T32S R2W S3 CS BT in double scribe bears N.30½°W., 19.6'

    11" D.Fir scribed T32S R2W S2 CS BT in double scribe bears N.52°E., 27.8'

    8" cedar scribed T32S R2W S11 CS BT in double scribe bears S.50½°E., 29.7'

We set stone beside cap  
Dec. 20°