

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7614)

-----

Set an ironstone 24x10x4 ins., 18" in the ground for cor. of secs. 35 and 36, marked with one notch on the E. and 5 notches on W. edges, from which

A Fir 24" dia., bears N.67½°E., 42 lks. dist. mkd. T31S R2W S36 BT.

A Fir 24" dia., bears N.63°W., 43 lks. dist. mkd. T31S R2W S35 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616; 7630-31; 7638)

-----

(Page 7616)

The cor. of secs. 35 & 36, which is an ironstone 6x8x4 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.

(Pages 7630-31)

The old cor. of secs. 35 & 36.

I destroy the cor. and marks on bearing trees.

(Page 7638)

Intersect N. bdy. of the township (T32-2) 35.50 chs. N.89°58'E., of the closing cor. of secs. 2 & 3.

Set a basalt stone 15x10x5 ins., 10" in the ground for closing cor. of secs. 35 and 36, marked CC on N. with 1 groove on E. and 5 grooves on W. face, from which

A Fir 16" dia., bears N.30°E., 30 lks. dist. mkd. T31S R2W S36 BT.

A Fir 30" dia., bears N.45°W., 5 lks. dist. mkd. T31S R2W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Conell, crew - July 1966 - C.S. File 54/28-48

-----

Found - Stone at sec. corner, no marks legible.

30" D.Fir now 38", N.45°W., 3.3 ft., shows good scar.

16" D.Fir N.30°E., 19.8 ft. Tree down with burned face, scribe marks visible. (Find brg. to be N.65°E., 19.8 ft.)

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W

S 35 | S 36

S 2 T32S

1966

(Cont. Next Page)

