

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 19 Page(s) 8297

Set an ironstone 24x12x8", 18" in the ground" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which
A fir, 16" dia., bears N.86°E., 45 lks., mkd: 1/4 S24 BT.
A fir, 14" dia., bears S.33°W., 43 lks., mkd: 1/4 S23 BT.

R. Frost, G. Cunningham, D. Gaylord (USFS) - June 17, 1975
Approved by: Ed McGinty (Jackson) Co. Surveyor - C.S. File 58/101

Found - Firmly set, the 14x8x10" stone, projecting 3" & mkd. "1/4" on West face. Recorded as 24x12x8" by C.L. Campbell in 1902.

New - I replaced said stone with a 1x36" G.I. pipe set 26" in the ground with a 2 1/2" bronze disc mkd.:

JACKSON COUNTY 1975

T32S R2W

1/4 S

23|24

Original BTs fd. as follows:

A W.Fir, 25" dia., with healed blaze, bears record, N.86°E, 29.70 ft. to center of tree.

A W.Fir, 30" dia. with healed blazes, bears S.24°W, 28.38 ft. to center of tree. Rec S.33°W. 28.38 ft

I deposit orig. stone alongside as a memorial, mkd. new trees CS BT and take measurements to center of trees at lower blaze

W.Fir, 13" dia., bears S.6 1/2°E., 19.15 ft.

W.Fir, 12" dia., bears N.63 1/2°W., 13.27 ft.

Corner lies 40 ft North of small draw, & about 1,000 ft North of location marker on 30" dia. Fir snag, alongside road.

V = 18 1/4°