

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor Secs 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO rec Vol. 19 Pg) 8299

Set an ironstone 18x12x8", 12" in the ground for cor. of secs. 11, 12, 13, & 14 mkd with 4 notches on S & one notch on E edges, from which
 A fir, 30" dia. bears N.79°E., 97 lks mkd: T32S R2W S12 BT
 A fir, 10" dia., bears N.60½°E., 72 lks., mkd: T32S R2W S13 BT.
 A fir, 12" dia. bears S.59°W., 24 lks mkd: T32S R2W S14 BT
 A fir, 12" dia. bears N.42°W., 29 lks mkd: T32S R2W S11 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby & Wm. Stoffel - March 1963 - C.S. File 53/15-4

Found - Orig. 12", now 18", Fir Stump S.59°W. 15.8 ft., shows good scribing.
 Find Stump Sections for the other BTs.
 Find Stone as recorded.
Set - Brass Cap alongside Corner Stone & Mkd:
 County Surveyors Office 1963
 S 11 | S 12
 S 14 | S 13 T32S R2W
New BTs- 8" Fir bears N.25°E. 37.5 ft. scribed S12 T32S R2W CS BT
 15" W. Fir bears S.37°W. 66.5 ft. scribed S14 T32S R2W CS BT.
 16" Hemlock bears N.63°W. 68.2 ft. scribed S11 T32S R2W CS BT.
 12" W. Fir bears S.17°E. 68.5 ft. scribed S13 T32S R2W CS BT.

Fd. Ok Aug. 1970, DCSO VRT C.S. File 54/117
Fd. Ok 7/23/1973 DCSO VRT C.S. File 56/34-15

John Ransom, USFS - Jonathan Drew - 12/2013 - C.S. 65/85-34

Found - 2½" brass cap on 1" iron pipe, projecting 6" above a mound of stone.
 22" Fir N.25°45'E., 37.3 ft healed lower blaze, scribe visible on partially healed upper blaze
 19" Fir stump (S.37°W.) (66.5 ft) high stump, healed double blaze not visible from corner
 29" root hole N.65°W. 68.7 ft hemlock windthrown healed double blaze, large root hole
 23" Fir S.16°30'E. 90.0 ft healed double blaze (rec. 68.5 ft -FS verified fd dist)
 () = Record per M56-73 continued next page

