

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 20 Page(s) 8304)

Intersect S. bdy. of T31S R2W, 140 lks. E. of the ¼ sec. cor. on the S. bdy. of sec. 36.

At point of intersection, Set a basalt stone, 24x15x5 ins., 18" in ground, for closing cor. of secs. 1 and 2, mkd. CC on the S. face, with 1 groove on E. and 5 grooves on W. faces, from which

A Fir 14" dia., bears S.70½°E., 40 lks. dist. mkd. T32S R2W S1 BT.

A Fir 14" dia., bears S.3°W., 28 lks. dist. mkd. T32S R2W S12 BT.

Fd. and used in GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7615)

Survey by Bruce A. Shaner - For: Umpqua National Forest - Oct. 31, 1970 - RM 2-21

Found - Original corner stone.

12" orig. Fir BT, decayed stub, scribe visible bears S.3°W., 18.5 ft.

10" orig. Fir BT, decayed stub, scribe visible, bears S.70½°E., 26.4 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S T32S R2W
C C S2|S1
1970 O.P.E. 4906

Marked - 16" Fir bears S.27°W., 78.5 ft.

10" Fir bears S.79°E., 63.4 ft.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173-1