

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T32-1

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8246)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 14" dia., bears N.70°E., 46 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears S.60°W., 22 lks. dist. mkd. ¼ S BT.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Dec. 1976 - M 56-78

Set 2" x 30" I.P. with brass cap stamped "T32S R2W ¼ S13 S18 R1W OLS 536 1976."
New BTs- 12" Fir bears S.53°W., 31.2 ft. scribed ¼ S13 BT.
24" I.Cedar bears N.35°E., 17.3 ft. scribed ¼ S18 BT.

Found OK by R. Wytcherley, May 2004 - M144-50