

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, T32-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8246-47)

Set a Fir post 4½ ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 12, 13 and 18, mkd. T32S S7 on NE.; R1W S18 on SE.; R2W S13 on SW.; and S12 on NW. faces, with 2 notches on N. and 4 notches on S. edges, from which
A Fir 35" dia., bears N.58°E., 29 lks. dist. mkd. T32S R1W S7 BT.
A Fir 3" dia., bears S.74°E., 23 lks. dist. mkd. T32S R1W S18 BT.
A Fir 4" dia., bears S.65°W., 7 lks. dist. mkd. T32S R2W S13 BT.
A Fir 14" dia., bears N.58°W., 7 lks. dist. mkd. T32S R2W S12 BT.

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8300)

Intersect E. bdy of Tp., 19 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is a post, badly decayed and marks mostly all obliterated. The stumps of the SE. and SW. trees are standing. The NW. tree has fallen over. I reestablish this sec. cor. in the same place as follows:
Set a Fir post 6" sq., 3 ft. long for cor., marked T32S S7 on NE.; R1W S18 on SE.; S13 on SW.; and R2W S12 on NW. faces, with 2 notches on N. and 4 notches on S. edges, from which
A Fir 35" dia., bears N.58°E., 29 lks. dist. mkd. T32S R1W S7 BT.
A Fir 30" dia., bears S.50°E., 44 lks. dist. mkd. T32S R1W S18 BT.
A Fir 12" dia., bears S.31 3/4°W., 61 lks. dist. mkd. T32S R2W S13 BT.
A Fir 14" dia., bears N.29°W., 31 lks. dist. mkd. T32S R2W S12 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby & Wm. Stoffel, crew - Aug. 1963 - C.S. File 53/15-12

Found - Orig. 14" now 16" Fir stump, shows good reverse scribing, N.29°W., 20.5 ft.
Orig. 30" now 36" Fir snag S.50°E., 29.0 ft., shows good scribing.
Orig. SW. BT, not found.
Do find stump of orig. NE. BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, T32-1

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

<p>Set Brass cap at cor. mkd:</p> <p>Logging road 75 ft. South.</p> <p>New BTs- 5" Chinquapin bears N.38°W., 48.7 ft. scribed S12 CS BT.</p> <p style="padding-left: 40px;">12" Hemlock bears N.22°E., 49.6 ft. scribed S7 T32S R1W CS BT.</p> <p style="padding-left: 40px;">5" W.Fir bears S.86°E., 68.3 ft. scribed S18 CS BT.</p>	<p>County Surveyors Office</p> <p>T 32 S</p> <table border="1" style="margin: auto;"> <tr> <td>S 12</td> <td>S 7</td> </tr> </table> <p>R 2 W S 13 S 18 R1W</p> <p>1963</p>	S 12	S 7
S 12	S 7		
<p>Fd. OK, Aug. 1970, V. Tracy, DCSO - C.S. File 54/117-12</p>			
<p>Survey by Glenn S. Baughman - For: U.S. Forest Service - Dec. 1976 - M 56-69; M 56-70 and M 56-68</p> <p style="text-align: center;">-----</p> <p>Found - 1963 DCSO brass cap.</p> <p style="padding-left: 40px;">6" Chinquapin, dead, N.38°W., 48.7 ft.</p> <p style="padding-left: 40px;">20" W.Fir bears N.22°E., 49.6 ft.</p> <p style="padding-left: 40px;">36" Fir, snag, bears S.50°E., 29.0 ft.</p> <p style="padding-left: 40px;">6" W.Fir, stob, bears S.86°E., 68.3 ft.</p> <p>New BTs- 10" Fir bears N.85°W., 23.3 ft. scribed "T32S R2W S13 BT" with brass washer "LS 536".</p> <p style="padding-left: 40px;">9" Fir bears S.34°E., 21.6 ft. scribed "T32S R1W S18 BT" with brass washer "LS 536".</p> <p style="padding-left: 40px;">10" Fir bears N.15°W., 62.3 ft. scribed "T32S R2W S12 BT" with brass washer "LS 536".</p>			
<p>Survey by Glenn S. Baughman - For: U.S. Forest Service - July 1979 - C.S. File 58/176-41</p> <p style="text-align: center;">-----</p> <p>Found - 1" Iron pipe, projecting 24" above the ground with a 2½" brass cap mkd. by the County in 1963.</p> <p style="padding-left: 40px;">35" D.Fir rotted stump, bears N.58°E., 19.1 ft.</p> <p style="padding-left: 40px;">6" Chinquapin snag with scribe marks "S12 CS BT" visible, bears N.38°W., 48.7 ft.</p> <p style="padding-left: 40px;">20" W.Fir with healed blaze bears N.22°E., 49.6 ft.</p> <p style="padding-left: 40px;">36" Fir, wind thrown snag, bears S.50°E., 29.0 ft.</p> <p style="padding-left: 40px;">12" D.Fir with scribe marks "T32S R2W S13 BT" visible on a partially healed blaze, bears N.85°W., 23.3 ft.</p> <p style="padding-left: 40px;">10" D.Fir with scribe marks "T32S R1W S18 BT" visible on a partially healed blaze, bears S.34°E., 21.6 ft.</p> <p style="padding-left: 40px;">10" W.Fir with scribe marks "T32S R2W S12 BT" visible on a partially healed blaze, bears N.15°W., 62.3 ft.</p> <p style="text-align: right;">(Cont. Next Page)</p>			

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>New BTs- 10" D.Fir bears S.72°W., 40.3 ft. I marked "T32S R2W S13 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze. 12" D.Fir bears N.85°W., 23.3 ft. marked by Baughman in 1976. I chopped out "S13" and remarked "S12".</p>	
<p>Survey by Lloyd R. Moffit - For: U.S. Forest Service - June 1985 - C.S. File 63/8-17 -----</p> <p>Found - 1963 DCSO brass cap on a 1" iron pipe. 18" Fir, dead, bears N.22°E., 49.6 ft. blazes healed 14" Fir bears S.34°E., 21.6 ft. scribe visible. 13" Fir bears S.72°W., 40.3 ft. scribe visible. 15" Fir bears N.85°W., 23.3 ft. scribe visible. 6" Fir, dead, bears N.37°W., 48.7 ft. scribe visible. (Rec. Chinquapin)</p> <p>New BT - 7" Fir which bears N.01°E., 15.9 ft. scribed T32S R1W S7 BT.</p>	
<p>John Ransom, USFS - Jonathan Drew - 9/2013 - C.S. 65/85-31 -----</p> <p>Found - 2½" brass cap (properly mkd) on 1" iron pipe, projecting 12" above a 3 ft diameter mound of stone. 19" Fir S.69½°W., 40.4 ft healed double blaze. 21" Fir N.85°W., 23.1 ft healed double blaze. 14" Fir N.7¼°E., 16.0 ft healed single blaze. 24" Fir S.32¼°E., 22.1 ft scribe on part. healed double blaze Indt Fir stump N.27¼°W., 19.6 ft ax work on rotting stump Indt root hole N.21½°E., 50.1 ft no log found. Indt root hole N.38¾°W., 48.0 ft log with rotten face alongside Indt root hole N.61¾°E., 19.5 ft some remains of stump found. No new accessories established Red paint applied to BT faces and a 6" band at head height, BTs include BT & survey monument tags</p> <p>Note - Corner falls on north side of a graveled road, about 40 ft from centerline. Measurements to accessories made with LEICA 1103+ Total Station with reflectorless EDM to aluminum nail set at side center, and to center of found root holes, basis of bearing being plat record bearing (S.89°51'50"W.) Using steel line post found about 80 ft west of corner. Maintained line .5 miles east of corner. Cont.</p>	

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hellman -
6/3/2015 - C.S. File 65/90-28

-
- Found - A 2½" brass cap on 1¼" galvanized iron pipe, projecting 12" above a mound of stone.
Remains of an indt. Size fir stump bears, N.61°45'E., 19.5 ft, with no marks. (N.58°E., 19.1') 1883, (N.61°45'E., 19.5') 2013
Remains of an indt. Size fir stump bears, N.27°45'W., 19.6 ft, with ax work, rec. (N.29°W., 20.5') 1902, (N.27°45'W., 19.6') 2013
A root hole with rotted log alongside bears, N.38°45'W., 48.0 ft, rec. (N.38°W., 48.7') 1963, (N.38°45'W., 48.0') 2013
A root hole bears, N.21°30'E., 50.1 ft, with no trace of log, rec. (N.22°E., 49.6') 1963, (N.21°30'E., 50.1') 2013
A 21" fir bears, N.85°W., 23.1 ft, with a healed double blaze, rec (N.85°W., 23.3') 1976 (N.85°W., 23.1') 2013
A 25" fir bears, S.32°15'E., 22.1 ft, with scribe on part. Healed double blaze, rec. (S.34°E., 21.6') 1976, (S.32°15'E., 22.1') 2013
Remains of a rotten log with tags & no marks, no root hole found, rec. (N.15°W., - 62.3 ft) 1976 & 1979
A 20" fir bears, S.69°30'W., 40.4 ft, with a healed double blaze, rec. (S.72°W., 40.3') 1979, (S.69°30'W., 40.4') 2013
A 14" fir windfall bears, N.7°15'E., 16.0 ft, log lies west, rec. (N.1°E., 15.9') 1985, (N.7°15'E., 16.0') 2013

New - A 16" fir bears, N.73°30'E., 5.7 ft, mkd "T32SR1WS7" "BT" on a double blaze.
New BT includes ¾" brass washer mkd "ORPLS #89396" between B & T.

Corner maintenance/other info: clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

Geodetic coordinates:
LAT: N. 42°47'47.126" LONG: W. 122°52'24.475"
Ellipsoid height - 3215 ft
Datum - WGS 84
Source - Cell phone GPS, for navigation to corner