

PRIMARY CORNER DESCRIPTION Cor. No. 1 MT Top #1; MS 792

Alias \_\_\_\_\_ Description Cor. No. 3 MT Top #3; MS 792  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Mineral Survey No. 792 by C. Frank Rhodes, US Mineral Surveyor under instructions dated July 25, 1916 - (DCSO Recs. Vol. 28 Page(s) 11903)

-----  
The Cor. No. 1 identical with Cor. No. 2 Reddy lode and Cor. NO. 3, Gunnell lode, both unsurveyed, Umpqua Copper Co. claimant and with Cor. No. 1 of amended location.  
An alder post, 4.5 ft. long, 5" sq., set 1½ ft. in the ground scribed M T No. 1-1 M T No. 2-3-792; whence  
A fir, 14" dia., bears N.6°15'W., 20.80 ft. and  
A fir 12" dia., bears N.74°11'E., 15.60 ft., each blazed & scribed BT MT No. 1-1 M T No. 2-3-792  
The E ¼ sec. cor. of sec. 4, T32S R2W, WM, bears N.68°23'E., 1816.8 ft.

Douglas Co. Surveyors Office - Gary L. Langlitz - Frank C. Silagy - May 2, 1978 - C.S. File 60/11-4

-----  
Found - No trace of original Alder corner post.  
An orig. 14" D.Fir now a 20" stump with scribing "3 92" visible on previously opened blaze bears N.6°15'W., 20.80 ft.  
An orig. 12" D.Fir now a 16" snag with well healed single blaze bears N.81°E., 15.60 ft. (Rec. N.74°11'E., 15.60 ft)  
Set - At a point which agrees with measurements listed for the fd orig. corner accessories, WE SET a 1"x30" IP 28" in the ground with brass cap attached mkd:  
Douglas Co. Surveyor  
T 32 S  
MT 1-1 \ MS  
MT 2-3 / 792  
R 2 W  
1978  
New BTs- An 8" D.Fir scribed "MT 1-1 MT 2-3 MS 792 CS BT" on a double blaze bears N.52½°W., 14.9 ft.  
A 20" P. Pine scribed "MT 1-1 MT2-3 MS 792 CS BT" on a double blaze bears S.13°W., 60.3 ft.  
Corner located about 20 ft. north of a dirt road.