TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 985130

PRIMARY CORNER DESCRIPTION Cor. No. 1 Belle S; MS 792

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Mineral Survey No. 792 by C. Frank Rhodes, US Mineral Surveyor under instructions dated July 25, 1916 - (DCSO Recs. Vol. 28 Page(s) 11906)

Cor. No. 1, identical with Cor. No. 2 North Pole lode, unsurveyed and Cor. No. 4 Hales lode, unsurveyed, Umpqua Copper Company claimant and with Cor. No. 3 of amended location.

A fir post, 4.5 ft. long, 5" sq., set 1½ ft. in the ground scribed B S 1-792; whence

A fir, 20" dia., bears N.16°W., 31.75 ft. and

A fir 14" dia., bears N.13°38'E., 36.90 ft., each blazed and scribed BT B S 1-792.

The S. cor. of secs. 33 & 34, T32S R2W of WM bears N.0°47'E., 1771.1 ft.

Douglas Co. Surveyors Office - Gary Langlitz - Peter L. Earle - Frank Silagy - 4/6/1978 - C.S. File 59/46-23

Found - No trace of original fir corner post.

An Orig. 20" D.Fir, now a 30" snag, with scribing "S1 visible on previously opened blaze, bears N.16°W., 31.75 ft.

An orig. 14" D.Fir, now an 18" snag with well healed single blaze bears N.16°E., 36.90 ft. (Rec. N.13°38'E., 36.90 ft.)

Set - At a location which agrees with the previously described BTs WE SET a 1"x30" I.P. 24" in the ground with brass cap attached mkd:

DOUGLAS CO. SURVEYOR
1978
T32S
/ B S 1
/ M S 792
R2W

New BTs- A 12" D.Fir scribed "BS 1 MS 792 CS BT" on a double blaze bears N.40°W., 9.2 ft.

A 10" D.Fir, scribed "BS 1 MS 792 CS BT" on a double blaze, bears N.73½°E., 27.4 ft.