

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; and S. 12, T32-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8359)</p> <p>-----</p> <p>Set ¼ sec. post, from which</p> <ul style="list-style-type: none">A Fir 30" dia., bears N.60°E., 31 lks. dist.A Fir 24" dia., bears S.85°W., 31 lks. dist.					
<p>GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12787)</p> <p>-----</p> <p>The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree mkd. by Byars in 1871:</p> <ul style="list-style-type: none">A Fir 24" dia., bears S.85°W., 31 lks. dist., mkd. ¼ S3 on bark. <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"><tr><td>¼</td></tr><tr><td>S 12 S 7</td></tr><tr><td>R4W R3W</td></tr><tr><td>T32S</td></tr><tr><td>1959</td></tr></table> <p>from which a new bearing tree</p> <ul style="list-style-type: none">A Fir 18" dia., bears N.56¼°E., 66 lks., mkd. ¼ S7 BT.	¼	S 12 S 7	R4W R3W	T32S	1959
¼					
S 12 S 7					
R4W R3W					
T32S					
1959					
<p>Kris DeGroot - For Silver Butte Timber Co. - 8/2010 - M161-16</p> <p>-----</p> <p>Lat: 42°48'21.87468"N. Long: 123°06'41.75427"W.</p> <p>Found - USBLM BCIP by Hans W. Thielsen, Cadastral Surveyor, in 1959 per USBLM Field note Volume OR-R0571, pages 75 & 76, firmly set, projecting 10" above the ground, properly marked:</p> <p>from which the orig. BT by Byars IN 1871:</p> <ul style="list-style-type: none">A 36" Fir high-stump bears S.85°W., 21.3 ft (rec. 31 lks. - 20.5 ft) <p>and a BT by Thielsen in 1959:</p> <ul style="list-style-type: none">A 18" rotted fir stump bears N.56°15'E., 42.7 ft. (rec. 66 lks. - 43.6 ft) <p>New BTs-</p> <ul style="list-style-type: none">A 10" D.Fir bears N.52°E., 22.6 ft scribed "¼ S7 BT"A 10" D.Fir bears S.55°45'W., 12.6 ft scribed "¼ S12 BT" <p>New RMs-</p> <ul style="list-style-type: none">A 5/8"x30" iron rod bears S.80°18'00"E., 17.75 ft.A 5/8"x30" iron rod bears S.2°59'06"W., 23.95 ft.					