TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (Tsp. corner)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7785)

Set post, cor. to Tps. 31 and 32 South, Rgs. 3 and 4 W., from which

A Willow 5" dia., bears N.48°E., 14 lks. dist.
A Willow 5" dia., bears S.48°E., 11 lks. dist.
A Willow 5" dia., bears S.50°W., 9 lks. dist.
A Willow 5" dia., bears N.45°W., 13 lks. dist.

George J. Wenderoth, Deputy Co. Surveyor - For: H.D. Hauck - May 1955 - C.S. File 46/134

1¼" Iron pipe.
8" Thorn, S.77°E., 48.8 ft.
10" Hemlock S.33°40'W., 185.5 ft.
24" Fir N.12°20'W., 142.0 ft.

Douglas Co. Surveyors Office - John M. Powell and crew - Jan. 13, 1966 - C.S. File 52/63-54

Found - Iron pipe at corner which was out of ground.
8" Thorn, now 18" S.77°E., 48.8 ft., scribe visible "S6CS BT"
10" Hemlock now 12", S.33¼°W., 185.5 ft., scribe visible "BT
24" Fir stump, N.12°W., 142.0 ft.

Set Brass cap at twp. cor. mkd: County Surveyors Office

		T 31 S			
R	S	36	S	31	R
4	S	1	S	6	3
W		T 32 S			W
		1966			

New BTs -6" D.Fir N.2°E., 120.3 ft. scribed S31 CS BT.
11" Hemlock S.75°E., 62.9 ft. scribed T32S R3W S6 CS BT.

The best way to reach corner is to wade Cow Creek in the summer.

Fd. OK, by R. Brown, April 1993, M 112-72
FD. Ok by R. Brown, 2/2009 - M157-10

Ronald L. Rice, Ward NW - For: Seneca Jones Co. - Sept 2011 - C.S. File 65/74-17

Found - Douglas Co brass cap dated 1966 with the following accessories: continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (Tsp. corner)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

20" Hemlock stump bears S.33¼°W., 185.5' - scribing visible
24" Fir stump bears N.12°W., 142.0' - rotted face
28" D.Fir bears N.2°E 120.3' - healed face
Other accessories of record not found
New BT - 9" W.Fir bears S.86¾°E., 140.2' - scribed "T32S R3W S6 BT"