TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO recs Vol 20 Pg 8421)

Set a granite stone 18x12x10", 12" in the ground for ¼ sec. cor. mkd. ¼ on North face, from which
A fir, 24" dia., bears N.33°W., 19 lks., mkd: ¼ S30 BT.
A fir, 16" dia., bears S.87°E., 52 lks., mkd: ¼ S31 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-28

Found - 18x12x10" stone, firmly set, mkd: "¼" on north face.
Orig. 24" D.Fir, now stump, N.33°W., 12.5 ft. scribe visible.
Orig. 16" D.Fir, now stump, S.87°E., 34.3 ft.
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE ¼ S 30 DOUG. CO
S 31 JACK. CO
New BTs- 31" D.Fir N.7°E., 58.9 ft. mkd: "¼ S30 CS BT"
45" D.Fir N.81°E., 38.6 ft. mkd: "¼ S30 CS BT"
No trees in sec. 31 for good control, too far away in clear cut unit.

Jackson Co. Surveyors Office - Edward McGinty, Co. Surveyor - Oct. 4, 1988 - C.S. File 63/82-13

Found - 1969 Doug. Co. Surveyors brass cap on 1" galv. IP projecting 8" above ground.
The original 18x10x8" stone mkd. with "X" on top and "¼" on the side is found alongside corner.
Orig. 1913 BT, sawed Fir stump, 24" dia. with healed blazes, bears S.87°E., 32.44 ft. (Rec. 34.32 ft)
Orig. 1913 BT, Sawed fir stump, 42" dia. containing scribe marks including "¼" in partially exposed face bears N.34°45'W., 12.82' (Rec. N.33°W., 12.54 ft.)
32" D.Fir containing scribe marks in axed into upper face bears N.7°E., 57.26 ft. to center of tree at upper face. (Rec. 58.9') 1969
38" D.Fir with healed blazes bears N.78°E., 37.71 ft. to center of tree at lower blaze. (Rec. N.81°E., 38.6 ft.)
New BT - 11" D.Fir bears S.6°15'W., 5.0 ft. to center of tree at lower blaze.
Corner lies in re-prod. area, 15 ft. north of draw, c. S.28°W., and approx. 60 ft. S.60°W. of location marker on fir snag, alongside road.