

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8445)

Set a serpentine stone 15x12x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 10" dia., bears N.33°W., 19 lks., mkd: ¼ S19 BT.
A fir, 8" dia., bears S.3°W., 19 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-77

Found - 15x12x6 Corner Stone, in place, mkd: "¼" on North face.
8" D.Fir, now windfall, S.30°W., 12.5 ft., shows scribing
No trace of NW BT.

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE ¼ S 19
1969 S 30

New BTs- 6" Hemlock N.72°W. 11.5 ft. mkd: ¼ S19 CS BT.
28" D.Fir S.73°E. 28.2 ft. mkd: ¼ S30 CS BT.

This corner lies on a north slope about 300 ft. East of a ridge.