

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 19 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8447)

Set a quartz stone, 12x10x8" 8" in the ground, for ¼ sec. cor., on N bdy. of sec. 19, marked ¼ on S face; from which
A chinquapin, 6" dia., bears S.26°E., 33 lks mkd: ¼ S19 BT
A madrona, 6" dia., bears S.49°W., 31 lks., mkd: ¼ S19 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1969 - C.S. File 54/91-43

Found - 12x10x8" Stone, firmly set, mkd: "¼" on south face. 5", now 8" Chinquapin, S.26°E., 21.8 ft., opened previously, tree rotted out.
5", now 8" Laurel, S.49°W. 20.5 ft., opened for scribing.

Set - Brass Cap at Cor. mkd: County Surveyors T32S R3W
Office 1969 ¼ S 19

New BTs- 6" D.Fir S.24°W. 20.2 ft. mkd: "¼ S19 CSBT".
12" Laurel S.86°E. 27.7 ft. mkd: "¼ S19 CS BT".