

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 168400

PRIMARY CORNER DESCRIPTION South Cor. Secs. 17 & 18, only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8374)

-----  
Set post, cor. to secs. 17, 28, 19, & 20, from which  
A laurel, 16" dia., bears N.30°E., 80 lks.  
A S.Pine, 20" dia., bears S.40°E., 142 lks.  
A S.Pine, 20" dia., bears S.85°W., 230 lks.  
A S.Pine, 60" dia., bears N.2°W., 126 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8411)

-----  
Intersect point for cor. of secs. 17, 18, 19, & 20, located by reference to the BTs. All other traces of the cor. have disappeared. I reestablish this cor. in its orig. position for the cor. of Secs. 17 & 18 only, as follows:  
Set a serpentine stone 16x8x6", 11" in the ground for cor. of secs. 17 & 18 only, mkd with 5 notches on East edge, from which  
A fir, 10" dia. bears N.18°E., 12 lks mkd: T32S R3W S17 BT  
A fir, 8" dia., bears N.82°W., 23 lks mkd: T32S R3W S18 BT  
I destroy the marks on former BTs referring to Secs. 19 & 20

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 7/29/1969 - C.S. File 54/91-32

-----  
Found - 16x8x6" Stone with 5 notches on the East Face.  
8", now 11" D.Fir, N.82°W. 15.2 ft., scribe visible.  
10", now 12" D.Fir, N.18°E. 7.9 ft. shows good scar.  
Set - Brass Cap at Cor. mkd: County Surveyors T32S R3W  
Office S 18 | S 17  
1969 S 19  
New BT - 12" D.Fir 8.1 ft. mkd: "T32S R3W S19 CS BT"