

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8420-1)

Set a serpentine stone 18x8x8", 12" in the ground for cor. of secs. 29, 30, 31, & 32 mkd with 1 notches on South & 5 notches on East edge, from which
A fir, 15" dia. bears N.51°E., 46 lks mkd: T32S R3W S29 BT
A fir, 36" dia. bears S.41°E., 29 lks mkd: T32S R3W S32 BT
A cedar, 30" dia., bears S.16°W., 54 lks., mkd: T32S R3W S31 BT.
A Y.Pine, 30" dia., bears N.30°W., 33 lks., mkd: T32S R3W S30 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-51

Found - Corner Stone, 18x8x8, firmly set mkd: 1 notch on S. & 5 on the E.
Orig. 15", now 27" D.Fir, N.51°E. 30.4 ft., shows good scar.
Orig. 36", now 47" D.Fir, S.41°E. 19.1 ft., shows good scar.
Orig. 30", now 38" Cedar, S.16°W. 35.6 ft., scribe visible.
Orig. 30", now 34" Y.Pine, N.30°W. 21.8 ft., scribe visible.
Set - Brass Cap at Cor. mkd: County Surveyors Office 1969 T32S R3W S 30|S 29 S 31|S 32
All Bearing Trees OK and Tagged.

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2916, surveyed June/Nov. 2018 - (DCSO records Vol. 59 Pages 23929-23930 & T32-3 Plat 2021-1)

The cor. of secs. 29, 30, 31 and 32, perpetuated by the Douglas County Surveyors Office in 1969; monumented with an iron post, 1½" dia., firmly set, projecting 14" above ground with brass cap (properly) mkd.
from which original bearing trees
A fir, 36" dia., bears N.51°E. 30.4 ft with a healed blaze
A fir, 46" dia., bears S.38¾°E., 18.4 ft., with a healed blaze. (Record, S.41°E. 19.1 ft.)
A cedar, 45" dia., bears S.16°W., 35.6 ft. with a healed blaze.
A pine, 40" dia bears N.30°W. 21.8 ft with a healed blaze.