TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8443)

Set a granite stone 14x10x8", 9" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 6" dia., bears N.22°E., 13 lks., mkd: ¼ S29 BT.
A fir, 24" dia., bears S.58°W., 19 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug 1969 - C.S. File 54/91

Found - Corner stone, firmly set, 14x10x8, mkd: "¼" on west face.
Orig. 24" now 30" D.Fir S.58°W., 12.5 ft. shows good scar.
Orig. 6" now down D.Fir N.22°E., 8.6 ft.
Set Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE 1969 ¼ S 30|S 29
New BT - 6" D.Fir N.14°E., 12.3 ft. mkd: "¼ S29 CS BT"

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2916, surveyed June/Nov. 2018 - (DCSO records Vol. 59 Pages 23929-23930 & T32-3 Plat 2021-1)

The ¼ sec. cor. of secs. 29 and 30, perpetuated by the Douglas County Surveyor's Office in 1969; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground with brass cap (properly) mkd.
from which an original bearing tree
A fir, 35" dia., bears S.55°W., 12.5 ft., with a healed blaze. (Record, S.58°W.)
and a bearing tree mkd. by Douglas County Surveyor's Office
A fir, 8" dia., bears N.15¼°E., 12.5 ft., with a healed double blaze.