

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8443-4)

Set a serpentine stone 15x10x6", 10" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edges, from which
A madrona, 6" dia., bears N.7°E., 16 lks., mkd: T32S R3W S20 BT.
A chinquapin, 12" dia., bears S.3°E., 56 lks., mkd: T32S R3W S29 BT.
A fir, 6" dia., bears S.60°W., 37 lks., mkd: T32S R3W S30 BT.
A cedar, 6" dia., bears N.66°W., 18 lks., mkd: T32S R3W S19 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-55

Found - Corner stone, 15x10x6 in place and mkd.
Orig. 6" now 12" cedar N.66°W., 11.9 ft., opened & shows scribe "B"
6" fir, now 3" windfall, S.60°W., 24.4 ft. rotted & no scribing.
NE & SE BTs are gone.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE S 19 | S 20
1969 S 30 | S 29
New BTs- 6" Cedar S.10°W., 5.6 ft. mkd: T32S R3W S30 CS BT
6" Laurel N.22°E., 7.4 ft. mkd: T32S R3W S20 CS BT
30" D.Fir S.16°E., 78.9 ft. mkd: T32S R3W S30 CS BT.
This corner lies approx. 85.0 ft. south of ravine.