

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8446)

-----

Set a serpentine stone 18x10x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 12" dia., bears S.29°E., 37 lks., mkd: ¼ S20 BT.

A fir, 8" dia., bears S.85°W., 38 lks., mkd: ¼ S19 BT.

Fd. stone & 2 BTs by Geo. Wenderoth, Deputy Co. Surveyor, 1945 - C.S. File 38/41A

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-54

-----

Found - Corner Stone, 18x10x6, in place & mkd: "¼" on west face.

Orig. 12" D.Fir, now 14" Snag, S.29°E. 24.4 ft., opened & found scribing.

Orig. 8", now 12" D.Fir, S.85°W. 25.1 ft., shows good axe face.

Set Brass Cap at Cor. Mkd: County Surveyors T32S R3W Office, 1969 ¼ S 19|S 20

New BT - 6" D.Fir N.87½°E. 22.5 ft. mkd: ¼ S 20 CS BT".

This corner lies on gentle grassy north slope.