

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8374)

-----  
Set ¼ sec. post, from which  
A fir 6" dia., bears N.88°E., 40 lks.  
A S.Pine 40" dia., bears S.75°W., 58 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8413)

-----  
Intersect point for the ¼ sec. cor. located by reference to the BTs. All other traces of the cor. have disappeared. I now reestablish this cor. in its orig. position as follows:  
Set a granite stone 16x12x4", 11" in the ground for ¼ sec. cor. mkd. ¼ on West face, from which  
A fir, 12" dia., bears N.79°E., 40 lks., mkd: ¼ S17 BT.  
A S.Pine, 48" dia., bears S.75°W., 62 lks., mkd: ¼ S18 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-35

-----  
Found - 16x12x4" Stone, firmly set, mkd: "¼" on west face.  
48" Pine, now stump, S.75°W. 40.9 ft.  
12", now 21" D.Fir, N.79°E. 26.4 ft., prev, opened, scribe visible.  
Set brass Cap at Cor. Mkd: County Surveyors T32S R3W  
Office, 1969 ¼ S 18|S 19  
New BT - 6" Y.Pine N.25°W. 39.1 ft. mkd: "¼ S18 CS BT".