

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8370)  
-----  
Set post, cor. to secs. 5, 6, 7 & 8, from which  
A fir, 24" dia., bears N.80°E., 20 lks.  
A fir, 20" dia., bears S.30°E., 41 lks.  
A fir, 16" dia., bears S.10°W., 42 lks.  
A fir, 16" dia., bears N.42°W., 14 lks.

Douglas Co. Surveyors Office - George Wenderoth, Deputy - H. Formand Witness - June 1950 - M27-15  
-----  
Find 24" fir S.10°W., 27.7 ft.  
18" fir N.45°W., 9.2 ft. OBT - corrected to N.54°45'W.  
30" fir S.22°30'E., 27.0 ft.  
Scribe - 10" hemlock N.36°30'E., 12.4 ft.  
Drive - 1¼" I.Pipe for corner.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 8/7/1969 - C.S. File 54/91-47  
-----  
Found - 1¼" pipe, 24" long, set at cor. 1950  
24" now 25" D.Fir S.10°W., 27.7 ft. shows good scar.  
30" now 35" D.Fir S.22½°E., 27.0 ft shows good scar.  
10" now 15" Hemlock, N.36½°E. 12.4 ft scribe visible  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W  
OFFICE S 6 | S 5  
1969 S 7 | S 8  
All BTs OK & tagged.  
This cor. lies E. slope about 150' S & 100' W of Snow Creek Rd. Location tag about 100 ft. north of sec cor. on west bank of road.

Leonard Herzstein, USFS & Deputy Co. Surveyor - Randy Lopez & Jim Hamilton - Nov. 23 & 25, 1981 - C.S. 61/29-33  
-----  
Found - 1" I.P., firmly set, projecting 12" above ground, w/B.C., (1969) properly marked, with a 1¼" Iron Pipe alongside  
BTs - 30" D.Fir, now a root-hole, bears S.22½°E., 27.0 ft., with 35" D.Fir log alongside, w/scribe marks visible on double bark blaze. (OBT)  
24" D.Fir, now root-hole, bears S.10°W. 27.7 ft with 25" D.Fir log alongside, w/healed dbl blaze (OBT)  
18" Fir, now 20" D.Fir bears N.54°45W., 9.2 ft., with healed double blaze. (OBT)  
10" Hemlock, now 17" bears N.36½°E., 12.4 ft. with healed double blaze. 1950 continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 15" W.Fir bears S.39½°E., 52.0 ft. scribed "T32S R3W  
S8 CSBT" on a double blaze.

Note - Corner lies on E. slope, about 100-ft. West and 150-  
ft. South of Snow Ck. Rd.

Fd. Ok by G. Lang - 7/1995 - M123-79