

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 228400

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 17 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8374-5)

Set ¼ sec. post, from which
A fir, 4" dia., bears N.20°W., 13 lks.
A laurel, 6" dia., bears S.45°W., 3 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8410-11)

Page 8410
... after careful search, I find no trace of the ¼ sec. cor.
Page 8410-8411
Apportioned distance
Set a granite stone 16x14x6", 11" in the ground for ¼ sec. cor. for Sec. 17 only, mkd. ¼ on North face, from which
A fir, 40" dia., bears N.77°E., 83 lks., mkd: ¼ S17 BT.
A fir, 14" dia., bears N.8°W., 51 lks., mkd: ¼ S17 BT.

Fd. stone & 2 BTs by Geo. Wenderoth, Deputy Co. Surveyor, 1945 - C.S. File 38/41A

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-52

Found - Corner Stone, 16x16x6 mkd: "¼" on north face.
Orig. 14", now 27" D.Fir, N.8°W. 33.4 ft., tree previously opened, pitched over scribe visible.
Orig. 40", now 43" D.Fir, N.77°E. 54.8 ft.

Set - Brass Cap at Cor. mkd: County Surveyors T32S R3W
Office ¼ S 17
1969

All Bearing Trees O.K. and Tagged.